



'basic' bi-directional ball valve

BIDIRECTIONAL BALL VALVE FEMALE - MALE SOLVENT SOCKET ITEM 789



REFERENCE	DESCRIPTION	Net weight	Volumen (m³)	Gross weight	Unidades lote
111D260	V.BID.S/ENC-ENC MACHO 20 FPM	0,165	0,01553	6,9267	40
111D261	V.BID.S/ENC-ENC MACHO 25 FPM	0,21	0,02244	8,8877	40
111D262	V.BID.S/ENC-ENC MACHO 32 FPM	0,353	0,03129	11,163	30
111D263	V.BID.S/ENC-ENC MACHO 40 FPM	0,606	0,03129	12,693	20
111D264	V.BID.S/ENC-ENC MACHO 50 FPM	0,865	0,03129	13,548	15
111D265	V.BID.S/ENC-ENC MACHO 63 FPM	1,444	0,03682	14,9892	10



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62




tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es



ITEM 789 | BIDIRECTIONAL BALL VALVE FEMALE - MALE SOLVENT SOCKET

CÓDIGO	f	PESO (g)	DN	A	B	C	D	E	F	PN	MEDIDA
11D260	20	153	15	95	55	16	74	80	44	PN16	MÉTRICO
11D261	25	193	20	103	62	19	80	80	49	PN16	MÉTRICO
11D262	32	322	25	132	72	23	103	101	66	PN16	MÉTRICO
11D263	40	556	32	143	88	25	125	130	71	PN16	MÉTRICO
11D264	50	810	40	165	103	31	138	130	75	PN16	MÉTRICO
11D265	63	1263	50	194	120	38	177	170	89	PN16	MÉTRICO





Product Documents



Product Certificates

Company Certificates



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62



tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es